

DISPARLON

February 2019

DISPARLON SPL-93

(Slipping/Leveling agent)

DISPARLON SPL-93 is a silicone based slip/leveling agent. DISPARLON SPL-93 has excellent compatibility to coatings without haze and improves slipping, scratch resistance, anti-blocking properties. It also prevents cratering, cissing and pin-hole that come from contamination taking full advantage of excellent leveling property.

ADVANTAGES

- Good leveling & DOI.
- Prevent crater & fish eye.
- Good dispersibility and stability on ageing in paint systems.

APPLICATIONS

DISPARLON SPL-93 can be used for all solvent based systems and it is especially recommended for Wood, Architectural and industrial top coatings such as Alkyd melamine, Acrylic melamine, Acrylic urethane.

INCORPORATION

Recommended levels : 0.2 ~ 2.0 % by weight on total formulation.
Method : Post addition on High speed dissolver is recommended.

TYPICAL PROPERTIES

Appearance : Colorless to light yellow liquid
Non-volatile : 15 % by wt.
Density : 0.89 g/cm³
Solvent : Xylene



Kusumoto Chemicals, Ltd.

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN

(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079

The information on use is based on data which are believed reliable, but any recommendation or suggestion made are without guarantee or warranty, since the conditions of use are outside our control. All products are sold on the conditions that purchasers shall make their own tests to determine the suitability of such products for their purpose and that all risks are assumed by user. We disclaim any responsibility for damages resulting from careless or improper handling or use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license. See SDS for safety handling before to use.

© 2009 All Rights Reserved By Kusumoto Chemicals, Ltd.