

*Additives for coatings and printing inks*  
**DISPARLON<sup>®</sup>**

Sep. 09, 2014

**DISPARLON<sup>®</sup> SPL-94**  
(Slipping / Leveling agent)

**DISPARLON SPL-94** is a silicone based slip / leveling agent. **DISPARLON SPL-94** has excellent compatibility to coatings without haze and improves slipping, scratch resistance, anti-blocking properties. It also prevents cratering, cissing and pin-hole that come from contamination taking full advantage of excellent leveling property.

**ADVANTAGES**

- Good leveling & DOI.
- Prevent crater & fish eye.
- Good dispersibility and stability on ageing in paint systems.

**APPLICATIONS**

**DISPARLON SPL-94** can be used for all solvent based systems and it is especially recommended for Wood, Architectural and industrial top coatings such as Alkyd melamine, Acrylic melamine, Acrylic urethane.

**INCORPORATION**

Recommended levels : 0.2 ~ 2.0 % by wt on total formulation.

Method : Post addition on High speed dissolver is recommended.

**TYPICAL PROPERTIES**

Appearance : Colorless to light yellow liquid  
Non-volatile : 15% by wt.  
Density : 0.89 g/cm<sup>3</sup> (at 20°C)  
Solvent : Xylene



*Kusumoto Chemicals, Ltd.*

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN

(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079