

Additives for coatings and printing inks
DISPARLON®

July 2024

DISPARLON® L-1982N
(Leveling/defoaming agent)

DISPARLON® L-1982N is a solvent-free leveling/defoaming agent composed of an acrylic copolymer, and can be used for a wide range of solvent/solvent-free coating systems. DISPARLON® L-1982N provides excellent leveling effect, prevents cratering and pinholes, and improves DOI. DISPARLON® L-1982N may have a defoaming effect in high-polar coating systems.

ADVANTAGES

- Improves leveling and DOI
- Prevents cratering and pinholes
- Defoaming effect
- Excellent recoatability
- Solvent-free
- Silicone-free

APPLICATIONS

DISPARLON® L-1982N can be used for a wide range of solvent/solvent-free coating systems.

INCORPORATION

- Additive levels : 0.1 – 0.5 wt% on total formulation.
The optimal additive level should be determined under an actual use condition.
- Method : Can be added at each production stage.

TYPICAL PROPERTIES

(The following figures are typical properties, not to be used for specification.)

Appearance	Clear to light yellow liquid
Active matter	100 %



Kusumoto Chemicals, Ltd.

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN

(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079

The information on use is based on data which are believed reliable, but any recommendation or suggestion made are without guarantee or warranty, since the conditions of use are outside our control. All products are sold on the conditions that purchasers shall make their own tests to determine the suitability of such products for their purpose and that all risks are assumed by user. We disclaim any responsibility for damages resulting from careless or improper handling or use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license. See SDS for safety handling before to use.

© 2004 – 2024 All Rights Reserved By Kusumoto Chemicals, Ltd.