

Additives for coatings and printing inks
DISPARLON®

August 2024

DISPARLON® 1958
(Defoamer)

DISPARLON® 1958 is a silicone-free defoamer composed of a low polarity/high molecular weight vinyl polymer. DISPARLON® 1958 has excellent defoaming effects and is particularly suitable for roller coating applications such as architectural paints.

ADVANTAGES

- Excellent defoaming effects
- Excellent recoatability
- Silicone-free

APPLICATIONS

DISPARLON® 1958 can be used in a wide range of solvent-borne ambient-cure systems such as alkyd, acrylic, acrylic urethane, polyester urethane, fluorine resin coatings, etc. It is also recommended for heavy duty coatings such as epoxies.

INCORPORATION

- Additive levels : 0.1 – 1.0 wt% on total formulation.
The optimal additive level should be determined under an actual use condition.
- Method : Can be added at each production stage.

TYPICAL PROPERTIES

Appearance	Light yellow liquid
Non-volatile matter	20 %
Density (20 deg.C)	0.81 g/cm ³
Solvent	Mineral spirits



Kusumoto Chemicals, Ltd.

11-13, UCHIKANDA 1-CHOME, CHIYODA-KU, TOKYO JAPAN
(TEL) 81-3-3292-8685 (FAX) 81-3-3295-6079

The information on use is based on data which are believed reliable, but any recommendation or suggestion made are without guarantee or warranty, since the conditions of use are outside our control. All products are sold on the conditions that purchasers shall make their own tests to determine the suitability of such products for their purpose and that all risks are assumed by user. We disclaim any responsibility for damages resulting from careless or improper handling or use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license. See SDS for safety handling before to use.

© 2008 – 2024 All Rights Reserved By Kusumoto Chemicals, Ltd.