Additives for coatings and printing inks DISPARLON®

October 2024

DISPARLON® 1970

(Leveling/defoaming agent for solvent-borne systems)

DISPARLON® 1970 is a leveling/defoaming agent composed of an acrylic copolymer, and is suitable for ambient-cure/baking systems. **DISPARLON®** 1970 provides excellent leveling effect, prevents cratering and pinholes, and improves DOI. **DISPARLON®** 1970 may have a defoaming effect in high-polar coating systems.

ADVANTAGES

- Improves leveling and DOI
- Prevents cratering and pinholes
- Defoaming effect
- Excellent recoatability
- Silicone-free

APPLICATIONS

DISPARLON® 1970 is recommended for general synthetic resin coatings and is especially suitable for medium-polar coating systems such as unsaturated polyester coatings, alkyd/melamine coatings, and acrylic/melamine.

INCORPORATION

Additive levels 0.2 - 1.0 wt% on total formulation.

The optimal additive level should be determined under an actual use condition.

Method : Can be added at each production stage.

Post-addition at a final production stage is recommended.

TYPICAL PROPERTIES

(The following figures are typical properties, not to be used for specification.)

The following figures are typical properties, not to be used for specification.	
Appearance	Clear to light yellow liquid
Non-volatile matter	40 %
Density (20 deg.C)	0.92 g/cm ³
Viscosity (20 deg.C)	75 mPa·s
Solvent	Xylene/Mineral spirits

Kusumoto Chemicals, Ltd.
11–13, UCHIKANDA 1–CHOME, CHIYODA–KU, TOKYO JAPAN
(TEL) 81–3–3292–8685 (FAX) 81–3–3295–6079